

PART NO. 125804BS

RG-58/U-4 Coaxial Cable, 1 x 0.8 mm

Detailed Specifications & Technical Data

CROSS SECTION



1 Conductor
2 Insulation
3 Screen
4 2nd Screen
5 Outer Jacket

CABLE CONSTRUCTION

Conductor	: 0.80 mm Ø electrolytic solid copper conductor
Insulation	: 2.95 mm Ø solid polyethylene
Screen	: Al/PET tape
2nd Screen	: Tinned copper braiding
Outer Jacket	: UV resistant PVC, halogen-free, polyethylene outer jacket

TECHNICAL DATA

Insulation Resistance	: >2000
Mutual Capacitance	: 50±2
Propagation Velocity	: 0,66
Operating Voltage	: 2.5
Test Voltage	: 5
Characteristic Impedance	: 53±3

STANDARDS

Manufacturing Std.	: MIL-C-17
Smoke Density Test	: IEC 61034-2 VDE 0482-1034-2 EN 61034-2
Corrosive Gas Test	: IEC 60754-2 VDE 0482-267-2-3 EN 50267-2-3
Halogen-free Test	: IEC 60754-1 VDE 0482-267-2-1 EN 50267-2-1
Flame Retardancy Test	: IEC 60332-1-2 VDE 0482-332-1-2 EN 60332-1-2

MECHANICAL CHARACTERISTICS

Bending Radius	: 15xD mm
Temperature Range Operating	: -40°C~+70°C

CABLE TYPE DATA

CAMCOM Part No.	Conductor Count	Conductor Diameter (mm)	Approx. Cable Diameter (mm)	Copper Weight (kg/km)	Approx. Weight (kg/km)	Packing Lengths (m)
125804BS	1	0.8	5	19.2	36	100/500/1000

PRODUCT VIEW



Camcom is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclamer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.