

# PART NO. 226016UNV

YSLY-JZ 0.45/0.75kV Control Cable, 16 x 6 mm²

## Detailed Specifications & Technical Data

### CROSS SECTION

1 Conductor
2 Insulation
3 Stranding
4 Outer Jacket

### TECHNICAL DATA

| | |
|---|---|
| Cross Section | : 6.0 mm² |
| Conductor Resistance Ω/km (20 °C) | : 3.30 |
| Insulation Resistance MΩ/km | : 20 |
| Current Carrying Capacity A | : 44 |
| Test Voltage V (DC, 1 minute) | : 2500 |
| Operating Voltage V DC | : 450/750 |

### CABLE CONSTRUCTION

| | |
|---|---|
| Conductor | : Stranded electrolytic annealed copper conductor (Class 5) (IEC 60228, EN 60228, DIN VDE 0295) |
| Insulation | : PVC (DIN VDE 0207, EN 50363-3, TS EN 50290-2-21 TI2), Black insulation, white number coded (DIN VDE 0293, TS EN 50334) |
| Stranding | : In layers |
| Outer Jacket | : UV resistant PVC outer jacket (EN 50363-4-1, DIN VDE 207 TM2). RAL 7001 (Grey) |

### STANDARDS

Flame Retardancy Test : IEC 60332-1-2 EN 60332-1-2 VDE 0482-332-1-2

### MECHANICAL CHARACTERISTICS

| | |
|---|---|
| Bending Radius | : 7.5xD mm |
| Temperature Range Operating | : -30°C~+70°C |

### CABLE TYPE DATA

| CAMCOM Part No. | Conductor Count | Conductor Cross-section (mm²) | Approx. Cable Diameter (mm) | Copper Weight (kg/km) | Approx. Weight (kg/km) | Packing Lengths (m) |
|---|---|---|---|---|---|---|
| 226016UNV | 16 | 6 | 28 | 823 | 1419 | 100/500/1000 |

### PRODUCT VIEW




**Camcom** is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclamer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.