PART NO. 2351UN

1-Pair 22AWG Unshielded PVC Cable

Detailed Specifications & Technical Data

CROSS SECTION



1 Conductor
2 Insulation
3 Outer Jacket

CABLE CONSTRUCTION

Conductor	: 22 AWG (Solid) Tinned Copper
No. of Conductors	: 2 (1 pairs)
Insulation	: Polyvinyl Chloride
Insulation Thickness	: 0.010 in (0.25 mm)
Insulation Diameter	: 0.046 in (1.2 mm)
Shield	: Unshielded
Outer Jacket	: Polyvinyl Chloride
Jacket Thickness	: 0.032 in (0.81 mm)
Cable Diameter	: 0.156 in (3.96 mm)

ELECTRICAL CHARACTERISTICS

Conductor DCR	: 20.6 Ohm/1000ft
Capacitance	: 30 pF/ft (98 pF/m)
Max Current	: 6 Amps per Conductor at 30°C
Voltage Rating	: 150 V

MECHANICAL CHARACTERISTICS

Operating Temperature	: -20°C to +80°C
Min. Bending Radius	: 1.6 in (41 mm)
Max. Pull Tension	: 16 lbs (7.3 kg)
Approx. Weight	: 12 lbs/1000ft

COLOR & PACKAGE

Jacket	: PVC
Packing	: 305 m / 500 m reels or drums

CABLE TYPE DATA

CAMCOM Part No.	Conductors	AWG	Shield	Jacket	Cable Ø	Approx. Weight
2351UN	2	22	No	PVC	3.96 mm	12 lbs/1000ft

Camcom is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclamer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.