PART NO. 2362BS

2 PAIR 22AWG braided shield RS-485 cable

Detailed Specifications & Technical Data

CROSS SECTION



1 Conductor
2 Insulation
3 Shield + Drain Wire
4 Outer Jacket

CABLE CONSTRUCTION

Conductor	: 22 AWG (7x30) Tinned Copper
No. of Conductors	: 4 (2 pairs)
Insulation	: Polyethylene (Foam) HDPE
Insulation Thickness	: 0.025 in (0.64 mm)
Insulation Diameter	: 0.079 in (2.0 mm)
Shield	: Bi-Laminate (Alum+Poly) Tape 100% + Tinned Copper Braid 65%
Drain Wire	: 22 AWG (7x30) TC
Outer Jacket	: Polyvinyl Chloride
Jacket Thickness	: 0.053 in (1.3 mm)
Cable Diameter	: 0.350 in (8.89 mm)

ELECTRICAL CHARACTERISTICS

Conductor DCR	: 18.2 Ohm/1000ft
Capacitance Cond-to-Cond	: 11 pF/ft (36 pF/m)
Characteristic Impedance	: 120 Ohm
Velocity of Propagation	: 78%
Max Current	: 4.8 Amps per Conductor at 30°C
Insertion Loss @ 1 MHz	: 0.5 dB/100ft
Voltage Rating	: 300 V

MECHANICAL CHARACTERISTICS

Operating Temperature	: -20°C to +60°C
Min. Bending Radius	: 4.2 in (110 mm) stationary and installation
Max. Pull Tension	: 80 lbs (36 kg)
Approx. Weight	: 58 lbs/1000ft

COLOR & PACKAGE

Jacket	: Polyvinyl Chloride
Packing	: 305 m / 500 m reels or drums

CABLE TYPE DATA

CAMCOM Part No.	Conductors	AWG	Shield	Jacket	Cable Ø	Approx. Weight
2362BS	4	22	Yes		8.89 mm	58 lbs/1000ft

Camcom is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclamer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.