

# PART NO. 320760IBE

LI2Y(St)CY-PiMF/TiMF Signal Control Cable, 10 x 2 x 0.75 mm²

## Detailed Specifications & Technical Data

### CROSS SECTION



1 Conductor
2 Insulation
3 Stranding
4 Individual Wrapping
5 Individual Screen
6 Wrapping
7 Screen
8 Outer Jacket

### CABLE CONSTRUCTION

| | |
|---|---|
| Conductor | : Stranded electrolytic copper conductor (Class 5) (IEC 60228, EN 60228, DIN VDE 0295) |
| Insulation | : Solid polyethylene (EN 50290-2-23, BS 6234 Type 03 – ASTM D 1248) (DIN 47100) |
| Stranding | : Screened pairs or triads are stranded in layers. |
| Individual Wrapping | : Polyester tape |
| Individual Screen | : Tinned copper earthing wire, Al/PET tape |
| Wrapping | : Polyester tape |
| Screen | : Al/PET tape, tinned copper braiding |
| Outer Jacket | : UV resistant PVC outer jacket. RAL 7035 (Grey) |

### TECHNICAL DATA

| | |
|---|---|
| Cross Section | : 0.75 mm² |
| Conductor Resistance (20 °C) Ω/km | : 26.0 |
| Insulation Resistance (20 °C) MΩ/km | : 5000 |
| Mutual Capacitance nF/km | : 120 |
| Operating Voltage V DC | : 300/500 |
| Test Voltage (@ 1 minute) V DC | : 2000 |

### STANDARDS

Flame Retardancy Test : IEC 60332-1-2, VDE 0482-332-1-2, BS EN 60332-1-2

### MECHANICAL CHARACTERISTICS

| | |
|---|---|
| Bending Radius | : 7.5xD mm |
| Temperature Range Operating | : -30°C ~ +70°C |

### CABLE TYPE DATA

| CAMCOM Part No. | Conductor Count | Pair Count | Conductor Cross-section (mm²) | Approx. Cable Diameter (mm) | Copper Weight (kg/km) | Approx. Weight (kg/km) | Packing Lengths (m) |
|---|---|---|---|---|---|---|---|
| 320760IBE | – | 10 | 0.75 | 20 | 225.6 | 374 | 100/500/1000 |

### PRODUCT VIEW




**Camcom** is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclamer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.