PART NO. 3404UN

4C 20AWG Unshielded LSZH Cable

Detailed Specifications & Technical Data

CROSS SECTION



1 Conductor

2 Insulation

3 Outer Jacket

CABLE CONSTRUCTION

Conductor	: 20 (7x28) Bare Copper
No. of Conductors	: 4
Insulation	: Polypropylene
Insulation Thickness	: 0.2 mm
Insulation Diameter	: 1.27 mm
Shield	: Unshielded
Outer Jacket	: Low Smoke Zero Halogen (Flame Retardant)
Jacket Thickness	: 0.4 mm
Cable Diameter	: 4.10 mm

ELECTRICAL CHARACTERISTICS

Conductor DCR	: 34 Ohm/km
Capacitance	: 60 pF/m
Max Current	: 3 A
Voltage Rating	: 300 V

MECHANICAL CHARACTERISTICS

Operating Temperature	: -20°C to +70°C
Min. Bending Radius	: 41 mm (installation) / 20 mm (setting)
Max. Pull Tension	: 90 N

COLOR & PACKAGE

Jacket	: LSZH
Packing	: 305 m / 500 m reels or drums

CABLE TYPE DATA

CAMCOM Part No.	Conductors	AWG	Shield	Jacket	Cable Ø	Approx. Weight
3404UN	4	20	No	LSZH	4.10 mm	-

Camcom is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands

+31708910864

sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclamer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.