PART NO. 3408FS

8C 20AWG Shielded LSZH Cable

Detailed Specifications & Technical Data

CROSS SECTION



1 Conductor
2 Insulation
3 Shield + Drain Wire
4 Outer Jacket

CABLE CONSTRUCTION

Conductor	: 20 AWG (7x28) Bare Copper
No. of Conductors	: 8
Insulation	: Polyolefin
Insulation Thickness	: 0.2 mm
Insulation Diameter	: 1.25 mm
Shield	: Bi-Laminate (Alum+Poly), 100% coverage
Drain Wire	: 24 AWG (7x32) TC
Outer Jacket	: Low Smoke Zero Halogen (Flame Retardant)
Jacket Thickness	: 0.5 mm
Cable Diameter	: 5.60 mm

ELECTRICAL CHARACTERISTICS

Nom. Conductor DCR	: 34 Ohm/km
Nom. Capacitance Cond-to-Cond	: 110 pF/m
Nom. Capacitance Cond-to-Other	: 224 pF/m
Max. Current	: 2.7 Amps per Conductor
Nom Outer Shield DCR	: 24 Ohm/km

MECHANICAL CHARACTERISTICS

Operating Temperature	: -20°C to +70°C
Min. Bending Radius	: 5*D/10*D
Max. Pull Tension	: 200 N

COLOR & PACKAGE

Jacket	: LSZH
Packing	: 305 m / 500 m reels or drums

CABLE TYPE DATA

CAMCOM Part No.	Conductors	AWG	Shield	Jacket	Cable Ø	Approx. Weight
3408FS	8	20	Yes	LSZH	5.60 mm	-

Camcom is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclamer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.