PART NO. 3604UN

4C 16AWG Unshielded LSZH Cable

Detailed Specifications & Technical Data

CROSS SECTION



1 Conductor

2 Insulation

3 Outer Jacket

CABLE CONSTRUCTION

Conductor	: 16 (19x29) Bare Copper
No. of Conductors	: 4
Insulation	: Polypropylene
Insulation Thickness	: 0.2 mm (0.0079 in)
Insulation Diameter	: 1.8 mm (0.071 in)
Shield	: Unshielded
Outer Jacket	: Low Smoke Zero Halogen (Flame Retardant)
Jacket Thickness	: 0.4 mm (0.016 in)
Cable Diameter	: 5.35 mm

ELECTRICAL CHARACTERISTICS

Nom. Conductor DCR	: 13.8 Ohm/km (4.21 Ohm/1000ft)
Nom. Capacitance Cond-to-Cond	: 85 pF/m (26 pF/ft)
Max. Current	: 5 A

MECHANICAL CHARACTERISTICS

Operating Temperature	: -20°C To +70°C
Min. Bending Radius	: 53.5 mm
Max. Pull Tension	: 240 N (54 lbf)

COLOR & PACKAGE

Jacket	: LSZH
Packing	: 305 m / 500 m reels or drums

CABLE TYPE DATA

CAMCOM Part No.	Conductors	AWG	Shield	Jacket	Cable Ø	Approx. Weight
3604UN	4	16	No	LSZH	5.35 mm	-

Camcom is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclaimer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.