PART NO. 3703UN

3C 14AWG Unshielded LSZH Cable

Detailed Specifications & Technical Data

CROSS SECTION



1 Conductor

2 Insulation

3 Outer Jacket

CABLE CONSTRUCTION

Conductor	: 14 (19x27) bare copper
No. of Conductors	: 3
Insulation	: polyolefin
Shield	: Unshielded
Outer Jacket	: FRNC/LSZH
Jacket Thickness	: 0.4 mm (0.016 in)

ELECTRICAL CHARACTERISTICS

Max. Conductor DCR	: 8.3 Ohm/km (2.5 Ohm/1000ft)

MECHANICAL CHARACTERISTICS

Operating Temperature	: -30°C To +70°C

COLOR & PACKAGE

Jacket	: LSZH
Packing	: 305 m / 500 m reels or drums

CABLE TYPE DATA

CAMCOM Part No.	Conductors	AWG	Shield	Jacket	Cable Ø	Approx. Weight
3703UN	3	14	No	LSZH	-	-

Camcom is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands

+31708910864

sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclaimer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.