PART NO. 3704FS

4C 14AWG Shielded LSZH Cable

Detailed Specifications & Technical Data

CROSS SECTION



1 Conductor
2 Insulation
3 Shield + Drain Wire
4 Outer Jacket

CABLE CONSTRUCTION

Conductor	: 14 (19x27) Bare Copper
No. of Conductors	: 4
Insulation	: Polypropylene
Insulation Thickness	: 0.28 mm (0.011 in)
Insulation Diameter	: 2.34 mm (0.0921 in)
Shield	: Tape - Bi-Laminate (Alum+Poly), 100% coverage
Drain Wire	: 24 AWG (7x32) TC
Outer Jacket	: Low Smoke Zero Halogen (Flame Retardant)
Jacket Thickness	: 0.5 mm (0.020 in)
Cable Diameter	: 7.0 mm (0.28 in)

ELECTRICAL CHARACTERISTICS

Conductor DCR	: 8.3 Ohm/km (2.5 Ohm/1000ft)
Capacitance Cond-to-Cond	: 120 pF/m (37 pF/ft)
Capacitance Cond-to-Other	: 220 pF/m (67 pF/ft)
Max. Current	: 6.4 Amps per Conductor
Voltage Rating	: 300 V

MECHANICAL CHARACTERISTICS

Operating Temperature	: -20°C To +70°C
Min. Bending Radius	: 70 mm (2.8 in)
Max. Pull Tension	: 480 N (110 lbf)

COLOR & PACKAGE

Jacket	: LSZH
Packing	: 305 m / 500 m reels or drums

CABLE TYPE DATA

CAMCOM Part No.	Conductors	AWG	Shield	Jacket	Cable Ø	Approx. Weight
3704FS	4	14	Yes	LSZH	7.0 mm	-

Camcom is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclamer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.