PART NO. 3704UN

4C 14AWG Unshielded LSZH Cable

Detailed Specifications & Technical Data

CROSS SECTION



1 Conductor

2 Insulation

3 Outer Jacket

CABLE CONSTRUCTION

Conductor	: 14 AWG (7x26) Bare Copper
No. of Conductors	: 4
Insulation	: Polypropylene
Insulation Thickness	: 0.28 mm (0.011 in)
Insulation Diameter	: 2.34 mm (0.0921 in)
Shield	: Unshielded
Outer Jacket	: Low Smoke Zero Halogen (Flame Retardant)
Jacket Thickness	: 0.4 mm (0.016 in)
Cable Diameter	: 6.8 mm (0.27 in)

ELECTRICAL CHARACTERISTICS

Nom. Conductor DCR	: 8.3 Ohm/km (2.5 Ohm/1000ft)
Nom. Capacitance Cond-to-Cond	: 75 pF/m (23 pF/ft)

MECHANICAL CHARACTERISTICS

Operating Temperature	: -20°C To +70°C
Min. Bending Radius	: 68 mm (2.7 in)

COLOR & PACKAGE

Jacket	: LSZH
Packing	: 305 m / 500 m reels or drums

CABLE TYPE DATA

CAMCOM Part No.	Conductors	AWG	Shield	Jacket	Cable Ø	Approx. Weight
3704UN	4	14	No	LSZH	6.8 mm	-

Camcom is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands

+31708910864

sales@camcom.co.nl

Disclaimer :- Datasheet is subject to modification without prior notication

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

© Technovation Alliance Enterprise B.V.