

# PART NO. 420550ISB

RE-Y(St)YSWBY-PiMF/TiMF Instrumentation Cable, 0.50 mm²

## Detailed Specifications & Technical Data

### CROSS SECTION



1 Conductor
2 Insulation
3 Individual Stranding
4 Individual Wrapping
5 Individual Screen
6 Overall Stranding
7 Overall Wrapping
8 Overall Screen

### CABLE CONSTRUCTION

| | |
|---|---|
| Conductor | : Stranded electrolytic copper conductor (Class 2) (IEC 60228, EN 60228, DIN VDE 0295) |
| Insulation | : PVC (BS EN 50290-2, VDE 0207 YI1), Black, White, Red; Number coded (BS 5308-2) |
| Individual Stranding | : Insulations stranding into pairs or triads |
| Individual Wrapping | : Polyester tape |
| Individual Screen | : Tinned copper earthing wire, Al/PET tape |
| Overall Stranding | : Screened pairs or triads are stranded in layers. |
| Overall Wrapping | : Polyester tape |
| Overall Screen | : Tinned copper earthing wire, Al/PET tape |
| Inner Jacket | : PVC inner jacket. RAL 9005 (Black) |
| Armor | : Galvanized steel wire braiding |
| Outer Jacket | : UV resistant PVC outer jacket. RAL 9005 (Black) |

### TECHNICAL DATA

| | |
|---|---|
| Conductor Diameter | : 0.50 mm² |
| Conductor Resistance Ω/km (20 °C) | : 36.0 |
| Insulation Resistance (@500V DC) MΩ/km | : 100 |
| Mutual Capacitance nF/km | : 160 |
| Operating Voltage V DC | : 300/500 |
| Test Voltage (@ 1 minute) V DC | : 2000 |

### STANDARDS

| | |
|---|---|
| Manufacturing Referance | : EN 50288-7 or IEC 60502-1 |
| Flame Retardancy Test | : IEC 60332-1-2 |

### MECHANICAL CHARACTERISTICS

| | |
|---|---|
| Bending Radius | : 7.5xD mm |
| Temperature Range Operating | : -30°C ~ +70°C |

### CABLE TYPE DATA

| CAMCOM Part No. | Conductor Size / Type |
|---|---|
| 420550ISB | 0.50 mm² |

### PRODUCT VIEW




**Camcom** is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclamer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.