

PART NO. 608000UN

Drop Wire Aerial Outdoor Telephone Cable, 0.80 mm

Detailed Specifications & Technical Data

CROSS SECTION



1 Conductor
2 Messenger Wire
3 Outer Jacket- Linear low-density or

TECHNICAL DATA

Conductor Diameter	: 0.80 mm
Conductor Resistance Ω/km (20 °C) – Maximum Average	: 28,96
Insulation Resistance	: >15000
Dielectric Strength – V (DC, 1 minute) – Pair – Pair	: 5600
Dielectric Strength – V (DC, 1 minute) – Pair – Screen	: 5600

CABLE CONSTRUCTION

Conductor	: Electrolytic annealed tinned copper (TS 3544, IEC28, ASTM B3)..
Messenger Wire	: Galvanized steel messenger wire (ASTM A 475-66T).
Outer Jacket- Linear low-density or medium-density, UV resistant black polyethylene outer jacket (ASTM D 1248).	

CABLE TYPE DATA

CAMCOM Part No.	Conductor Size / Type
608000UN	0.80 mm

PRODUCT VIEW



Camcom is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclamer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.