

PART NO. 610000FB

JE-2Y(St)C2Y xDSL Telecom Cable

CAMCOM™

Detailed Specifications & Technical Data

CROSS SECTION



1 Conductor
2 Insulation
3 Stranding
4 Wrapping
5 Screen
6 Outer Jacket

CABLE CONSTRUCTION

Conductor	: Electrolytic solid copper conductor.
Insulation	: Solid polyethylene insulation
Stranding	: Pair stranding, pairs are stranded into groups
Wrapping	: Polyester tape
Screen	: Tinned copper earthing wire, Al/PET tape, tinned copper braiding
Outer Jacket	: UV resistant polyethylene outer jacket. RAL 9004 (Black)

TECHNICAL DATA

Conductor Diameter Ω/km	: 146
Insulation Resistance MΩxkm (500 V DC)	: 2000
Mutual Capacitance nF/km	: 56
Capacitance Unbalance	: %2
Dielectric Strength V	: 1000
Operating Voltage V	: 250
Test Voltage V	: 1200
Capacitance Unbalance pF/500m	: 200
Characteristic Impedance Ω	: 100±10

MECHANICAL CHARACTERISTICS

Bending Radius	: 10xD mm
Temperature Range Operating	: -55°C~+70°C

CABLE TYPE DATA

CAMCOM Part No.
610000FB

ELECTRICAL PROPERTIES

Frequency MHz	Insertion Loss dB/100m (Max.)	Near-end Crosstalk (NEXT) Loss dB (Min.)	Propagation Dela y 5 n/m
1	≤30	≥55	≤6
10	≤100	≥45	≤5.7
16	≤110	≥40	
20	≤120	≥38	
30	≤160	≥35	

PRODUCT VIEW



Camcom is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclamer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.