

PART NO. 628008FSL

J-Y(St)Y Lg Fire Alarm Cable, 8 x 2 x 0.8 mm

Detailed Specifications & Technical Data

CROSS SECTION



1 Conductor
2 Insulation
3 Stranding
4 Wrapping
5 Screen
6 Outer Jacket

CABLE CONSTRUCTION

Conductor	: Class 1 electrolytic solid copper (IEC 60228, DIN VDE 0295, EN 60228)
Insulation	: PVC compound (VDE 0815, EN 50290-2-26)
Stranding	: Two pairs are stranded into a star-quad, above two pairs are stranded together in layers
Wrapping	: Polyester tape
Screen	: Tinned copper earthing wire, Al/PET tape
Outer Jacket	: Ultraviolet-resistant PVC outer sheath. RAL 3000 (Red)

TECHNICAL DATA

Conductor Diameter	: 0.80 mm
Conductor Resistance Ω/km (20 °C)	: 73.2
Insulation Resistance (@500V DC) MΩ/km	: 100
Mutual Capacitance nF/km	: 100
Operating Voltage V DC	: 300
Test Voltage (@ 1 minute) V DC	: 800

STANDARDS

Flame Retardancy Test : IEC 60332-1-2, VDE 0482-332-1-2, BS EN 60332-1-2

MECHANICAL CHARACTERISTICS

Bending Radius	: 10xD mm
Temperature Range Operating	: -30°C ~ +70°C

CABLE TYPE DATA

CAMCOM Part No.	Pair Count	Conductor Diameter (mm)	Cross-section (mm^2)	Average Cable Diameter (mm)	Copper Weight (kg/km)	Average Weight (kg/km)	Packaging Lengths (m)
628008FSL	8	0.8	–	10.7	77.3	141	100/500/1000

PRODUCT VIEW



Camcom is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclaimer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.