


# PART NO. 744000UNC

SIF Silicone Cable, 4.00 mm²

CAMCOM™

## Detailed Specifications & Technical Data

### CROSS SECTION



1 Conductor
2 Insulation

### TECHNICAL DATA

| | |
|---|---|
| Conductor Diameter | : 4.00 mm² |
| Conductor Resistance Ω/km (20 °C) | : 4.95 |
| Operating Voltage V DC | : 300/500 |
| Test Voltage (@ 1 minute) V DC | : 2000 |

### MECHANICAL CHARACTERISTICS

| | |
|---|---|
| Bending Radius | : 8xD mm |
| Temperature Range Operating | : -60°C ~ +250°C |

### CABLE CONSTRUCTION

| | |
|---|---|
| Conductor | : Stranded electrolytic tinned copper conductor (Class 5) (IEC 60228, EN 60228, DIN VDE 0295) |
| Insulation | : Silicone compound (EN 50363-2-1 EM9) |

### STANDARDS

| | |
|---|---|
| Smoke Density Test | : IEC 61034-2, VDE 0482-1034-2, BS EN 61034-2, BS EN 61034-2 |
| Corrosive Gas Test | : IEC 60754-2, VDE 0482-754-2, EN 60754-2, BS EN 60754-2 |
| Halogen-free Test | : IEC 60754-1, VDE 0482-754-1, EN 60754-1, BS EN 60754-1 |
| Flame Retardancy Test | : IEC 60332-1-2, VDE 0482-332-1-2, EN 60332-1-2, BS EN 60332-1-2 |
| Flame Propagation Test | : IEC 60332-3-24, VDE 0482-332-3-24, EN 60332-3-24, BS EN 60332-3-24 |
| Fire Resistance Test (FE180) | : IEC 60331-21 |

### CABLE TYPE DATA

| CAMCOM Part No. | Conductor Size / Type |
|---|---|
| 744000UNC | 4.00 mm² |

### PRODUCT VIEW




**Camcom** is proud to be certified by

Frame Offices - HQ, Alexanderveld 5-9,
2585 DB, Den Haag, Netherlands
+31708910864
sales@camcom.co.nl

Designed in Netherlands & Produced Globally.

Prepared By : Steve Smith

Disclamer :- Datasheet is subject to modification without prior notication

© Technovation Alliance Enterprise B.V.